



# TECHNICAL DATA SELECTION



65

72

BASIC VEHICLE (STANDARD)	Ducato 35 L	Ducato 35 L
Chassis / Low-Frame chassis	Fiat / AL-KO	Fiat / AL-KO
Cylinder / cubic capacity, ccm	4 / 2,287	4 / 2,287
Performance, kW / hp	96 / 130	96 / 130
Tank volume diesel, l	60	60
Wheel base, mm	3,980	3,980
DIMENSIONS	A-Class	Low-Profile
Total length, cm	645	724
Total width, cm	230	230
Total height, cm	289	289
headroom, cm	198	198
WEIGHT SPECIFICATIONS DUCATO 35 L	A-Class	Low-Profile
Mass when ready for driving, kg	2,990 <sup>1</sup>	2,990 <sup>1</sup>
Max. perm. total mass, kg	3,500	3,500
Payload, kg	510	510
Trailer load braked / unbraked, kg	2,000 <sup>3</sup> / 750 <sup>3</sup>	2,000 <sup>3</sup> / 750 <sup>3</sup>
Max. perm. mass of the combination, kg	5,500	5,500
WEIGHT SPECIFICATIONS DUCATO 35 L	A-Class	Low-Profile
Mass when ready for driving, kg	2,990 <sup>1</sup>	2,990 <sup>1</sup>
Max. perm. total mass, kg	3,850	3,850
Payload, kg	860	860
Trailer load braked / unbraked, kg	2,000 <sup>3</sup> / 750 <sup>3</sup>	2,000 <sup>3</sup> / 750 <sup>3</sup>
Max. perm. mass of the combination, kg	5,500	5,500
WEIGHT SPECIFICATIONS DUCATO 40 H		Low-Profile
Mass when ready for driving, kg	-	3,020 <sup>1</sup>
Max. perm. total mass, kg	-	4,500
Payload, kg	-	1,460
Trailer load braked / unbraked, kg	-	2,000 <sup>3</sup> / 750 <sup>3</sup>
Max. perm. mass of the combination, kg	-	6,000
CONFIGURATION		
Fresh water tank / waste water tank approx., l	120 <sup>4</sup> (20 l drive load) <sup>2</sup> / 100	120 <sup>4</sup> (20 l drive load) <sup>2</sup> / 100
Battery capacity, Ah (20 h)	80	80
Refrigerator volume approx., l	140	140
Heating	Truma Combi CP Plus	Truma Combi CP Plus

1) The vehicle mass when ready for driving has been determined in accordance with Reg (EU) 1230/2012, but reflecting the drive load of the fresh water tank (see Fn.2 and 4) and one aluminium gas bottle (11 kg)

2) Capacity of the fresh water tank acc. to Ann. V, part A, para. 2.6 Fn. (H) Reg (EU) 1230/2012, considering the 20 l drive load

3) Trailer load may vary depending on the configuration selected

4) Possible with the appropriate setting of the valve on the fresh water tank: max. 120 l

## General note

Information on weights and dimensions are implemented in accordance with Reg (EU) 1230/2012 provided that the catalogue including technical data and price list contains no contrary information.